



LY₂-80

铝合金液压双柱压力机. Hydraulic Machine

性能特点

- 用于铝合金门窗系列单模, 组合模具配套使用, 可完成各种相应普通型材, 异形型材的合型开模的冲裁加工。
- 通过液压油缸驱动摆杆传动控制两柱同步, 冲裁平稳, 精度高, 噪音小, 使用寿命长, 更换模具快捷、简便, 安全、可靠。

Product Features

- Lead for installation of aluminium alloy windows and doors, and the punching processing of aluminum profiles.....
- Through hydro-cylinder to drive balance staff in order to control two arm work at same time. Punching stability, high efficiency, low noise, no pollution and high precision. Easy to change moulds, quick, simple, safe and reliable.

技术参数 Technical Parameters

电源	Power supply	380V/50Hz
冲裁模位数	Punching capacity	12pcs
最大封闭高度	Max height	280mm
最小封闭高度	Min height	140mm
最大冲裁行程	Max travel	60mm
油缸直径	Oil tank diameter	80mm
油缸容量	Oil tank capacity	30L
电动机功率	Motor power	4.0kW
最大冲剪力	Max pressure	90kN
外形尺寸(L×B×H)	Dimension	1150×830×1140mm
机床重量	Weight	1000kg